

Befa-Handelsgesellschaft m.b.H.  
Hackengasse 31/1a  
A-1150 Wien

Produktion / factory:  
A-2061 Hadres 115

Telefon (+43) 1 479 02 08  
Telefax (+43) 1 479 02 08 - 17

[office@befa.net](mailto:office@befa.net)  
<http://www.befa.net>



## **Offer 240316-02**

### **Powder Filling Line PFB 2000**

To the filling of powder into plastic bags  
Reconditioned

The basic construction of the machine is manufactured from aluminum profiles.

All product-prominent parts are manufactured from stainless steel; therefore it is possible to fill also food.

The temperature of the welding cheeks is fully automatic regulated by temperature regulators. The packing process is controlled by a programmable flow control.

The packing foil is cutting off with color marks on the printed foil by a photo switch and it is checked with a length counter.

The dosing equipment works according to the volume principle and it is adjusted with screws.

The machine is conceived for continuous 3-shift operation with above operating conditions.



Befa-Handelsgesellschaft m.b.H.  
Hackengasse 31/1a  
A-1150 Wien

Produktion / factory:  
A-2061 Hadres 115

Telefon (+43) 1 479 02 08  
Telefax (+43) 1 479 02 08 - 17

[office@befa.net](mailto:office@befa.net)  
<http://www.befa.net>



## Technical Data:

Dimensions of the package:	width: 60 - 160 mm length: 100 - 350 mm depth: Pillow BAG
Output:	8 packages/min
Batching volume:	0,1 – 2,5 litre = 0,07 – 2,5 kg with a density 0,7 accuracy of filling: +/- 1,5%
Volumetric capacity of the holding tank:	25 litre
Working temperature of the welding cheeks:	140 - 180 °C
Compressed air supply:	6 Bar / 440 litre/min (27 m <sup>3</sup> /h)
Packing Material:	- bi-oriented polypropylene - BOPP - laminated polypropylene / polyethylene - PP/PE - metal sprayed foil - PP/AL/PE - thickness: 20 - 69 micron - diameter of the roll: 250 - 360 mm - diameter of the spindle: 78 mm
Noise level:	below 80 dB
Dimension of the machine:	height: 2800 mm length: 1200 mm width: 1600 mm
Weight of the machine:	320 kg
Operating conditions:	environmental temperature: +10°C - +35°C barometric pressure: 96 kPa +10%
Power supply:	400V / 50Hz / 1,6KW

**Price: 21.000,-**

All prices are ex works (Austria) and without VAT

All prices in EURO

Nonbinding offer, valid only after BEFA order confirmation.

Payment condition: has to be agreed

Best regards

**BEFA** Handelsgesellschaft m.b.H.  
Hackengasse 31/1A  
A-1150 Vienna, Austria  
Tel.: ++43-01-479 02 08  
Fax: ++43-01-479 02 08-17

Gerald Mayer